



# MGT-JDP-i800






1

### Inkjetted Circuit

Provide nano silver conductive ink, mask ink, etc.



2

### Inkjetted Devices


Preparation of devices based on various electronic inks



3

### Multi inkjet Head

Support multi-material inkjet patterned deposition



4

### Visual CCD Alignment


Visual CCD alignment, double-sided alignment printing, etc.



5

### Support Gerber file


Support TIF format and Gerber format file



6

### 3D Slice file


Supports slicing files, Stl/3mf/obj/3ds slicing tools



7

### Small Droplets


3pl small droplets, accurate ink droplet placement



8

### Open Waveform tool

waveform tools to adjust the waveform according to inks



9

### Independent ink pads


Independent ink pad to prevent contact contamination



10

### Printhead compatible

Good compatibility to water-based, oil-based, UV and solvent inks.



11

### High Resolution

Supports 1200DPI and 2400DPI, the smallest ink dot is about 50 microns



12

### Self-developed ink


Support self-developed various functional ink tests, open ink channels



13

### Variety of Printhead

Available in economical printhead and built-in heated printhead



14

### Functional platform

Heated vacuum platform, high temperature heating



15

### Line Trimming

Line trimmed to compensate for the wetting and spreading of droplets.



16

### UV light curing

UV curing for real-time curing of photosensitive functional resin ink.

# MGT-JDP-i800

Circuits Inkjet Printer



## Features

- Inkjet head: 2, (up to 4)
- Inkjet cap: 4 (separated)
- Small drop: 3pl
- Ink type: aqueous, solvent, UV
- Piezo waveform software: available
- Thinner trim function balances ink spread
- Vacuum adsorption and heatable platform

## Inks and Option

- Conductive ink
- Etch-resist UV ink
- Dielectric UV ink
- Support self-developed ink

## Applications

Applications include printed electronics, flexible electronics, organic electronics, and bioelectronics. It can be used to print and manufacture various microelectronic circuits, radio frequency antennas, 5G antennas, sensors, electric heating electrodes, etc., and can print and test OLED inks, TFE inks and quantum dot inks for touch screens and OLED/QLED lighting display fields.

## Tech data

Item	Content
Motion axis	3, (X, Y, Z)
Platform	Vacuum adsorption, heated
Inkjet size	297mm*210mm
Inkjet Height	0~10mm
Accuracy	±0.01mm
Inkjet head	2, (up to 4)
Drop volume	3.0pl
Ink type	Aqueous, solvent, UV
Inkjet lines	0.075mm ~0.1mm
Ink supply system	4 negative pressure ink supply systems
Ink caps	4 separated caps
File type	Gerber , ODB+ +*, 1 bit TIF
Resolution	1200*1200 、 2400*2400
Curing light	365nm UV
Power	220V / 50Hz, 1.5kw
Dimensions	Length ×Width×Height: 960mm×709mm×618mm
Equipment working conditions	Temperature Celsius: +20°C ~ +30°C Relative humidity 40% ~60%


\*Gerber, ODB++ format provides RIP software

# MGT-JDP-i800


## Circuit Inkjet Printer Use Cases



### Conductive ink ( MGT-IJP-INK3050 )



### Device Inkjet Preparation Solution



### Etch-resist UV ink ( MGT-UVI-ER103 ) and 3D Dielectric ink ( MGT-IST-UV70 )

